

KABELTABELL

MAKS KABELLENGDE - 1 FAS													
Motor			Kabel dimensjon - 70° C Isolasjon – Kobberleder mm2										
Volt	KW	HP	1.5	2.5	4	6	10	16	25	35	50	70	95
220 Volt	.25	1/3	190	320	510	770	1260	1970	2960	3990	5340	6970	8750
	.37	1/2	120	210	330	500	820	1290	1950	2640	3560	4680	5910
50 Hz	.55	3/4	80	140	230	350	580	900	1360	1830	2450	3210	4020
	.75	1.0	60	110	180	270	440	690	1050	1430	1930	2550	3230
	1.1	1.5	40	70	120	190	310	490	750	1020	1390	1860	2380
	1.5	2.0	30	60	100	150	250	400	620	850	1180	1590	2070
	2.2	3.0	20	40	60	100	170	270	410	560	770	1030	1320
	3.7	5.0	0	0	40	60	110	170	260	370	520	710	930

MAKS KABELLENGDE - 3 FAS																				
Motor			Kabel dimensjon - 70° C Isolasjon – Kobberleder mm2																	
Volts	KW	HP	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240	300	400	
220V 50Hz 3Ø 3-lead	.37	1/2	300	510	820	1230	2010	3160	4810	6540	8890									
	.55	3/4	200	350	550	830	1370	2150	3280	4460	6060	8060								
	.75	1	160	270	430	650	1070	1680	2550	3430	4710	6250	7970	9510						
	1.1	1.5	110	190	300	450	750	1170	1790	2430	3310	4400	5620	6700	7790	8970				
	1.5	2	80	140	230	340	570	900	1380	1880	2570	3430	4410	5290	6180	7150	8470	9670		
	2.2	3	50	90	150	230	380	600	950	1270	1740	2330	3000	3610	4230	4910	5840	6700	7790	
	3	4	40	70	110	170	280	440	670	920	1270	1700	2180	2630	3080	3570	4240	4850	5630	
	3.7	5	30	50	90	130	220	360	550	750	1030	1390	1790	2150	2520	2930	3480	4000	4640	
	4	5.5	30	50	80	120	200	320	490	670	920	1240	1590	1910	2240	2590	3070	3520	4070	
	5.5	7.5	0	30	60	90	150	240	380	520	710	960	1240	1490	1750	2040	2430	2790	3250	
	7.5	10	0	0	40	60	110	170	270	370	500	680	870	1050	1230	1420	1690	1930	2230	
	11	15	0	0	0	40	80	120	190	270	370	500	650	790	930	1080	1290	1490	1740	
15	20	0	0	0	0	60	90	150	200	280	380	500	610	720	840	1010	1170	1370		
18.5	25	0	0	0	0	0	70	110	160	220	300	390	480	570	650	800	920	1090		
22	30	0	0	0	0	0	60	100	130	190	260	330	400	480	560	670	780	910		
380v 50Hz 3Ø 3-Lead	.37	1/2	930	1550	2460	3670	6030	9460												
	.55	3/4	630	1050	1670	2500	4100	5860	9790											
	.75	1	490	820	1300	1950	3200	4330	7620											
	1.1	1.5	340	570	910	1360	2240	3200	5350	7280	9890									
	1.5	2	260	430	700	1040	1720	2340	4120	5630	7690									
	2.2	3	170	290	460	700	1150	1600	2770	3790	5190	6950	8950							
	3	4	120	210	340	510	840	1230	2030	2770	3790	5070	6530	7840	9190					
	3.7	5	100	170	270	410	680	980	1650	2260	3090	4140	5340	6420	7540	8750				
	4	5.5	90	150	250	370	610	920	1480	2020	2770	3700	4750	5710	6680	7740	9180			
	5.5	7.5	70	110	190	280	470	690	1140	1560	2140	2870	3700	4460	5240	6090	7250	8330	9700	
	7.5	10	50	80	130	200	330	530	810	1110	1510	2030	2610	3130	3670	4250	5040	5770	6680	
	11	15	0	60	90	140	240	360	590	810	1120	1510	1950	2350	2770	3230	3860	4450	5200	
	15	20	0	0	70	110	180	270	450	620	860	1160	1500	1820	2150	2520	3020	3490	4110	
	18.5	25	0	0	80	140	210	350	490	880	910	1190	1440	1700	1990	2390	2770	3260		
	22	30	0	0	0	0	120	180	300	410	570	770	1000	1210	1440	1680	2010	2330	2740	
	30	40	0	0	0	0	0	130	220	310	420	570	740	900	1060	1230	1470	1700	1990	
	37	50	0	0	0	0	0	110	180	240	340	460	590	710	840	980	1170	1350	1580	
45	60	0	0	0	0	0	0	150	200	280	380	490	600	700	820	980	1130	1330		
55	75	0	0	0	0	0	0	120	170	240	330	420	510	610	710	860	990	1170		
75	100	0	0	0	0	0	0	0	180	240	320	390	460	530	640	740	880			
90	125	0	0	0	0	0	0	0	0	190	240	290	350	400	480	550	650			
110	150	0	0	0	0	0	0	0	0	0	0	210	250	290	340	410	470	550		
130	175	0	0	0	0	0	0	0	0	0	0	180	220	260	300	360	420	500		
150	200	0	0	0	0	0	0	0	0	0	0	0	190	230	270	320	370	440		